


## HOSS WHITE RECT 30X90

| REFERENCE      | SIZE (cm) | THICKNESS (mm) | GROUP   |
|----------------|-----------|----------------|---------|
| <b>A039558</b> | 30X90     | 8,90           | REVESTI |



### DIMENSIONS AND SURFACE PROPERTIES

|                                                             |              |                                  |
|-------------------------------------------------------------|--------------|----------------------------------|
| Size, thickness, side straightness, flatness, orthogonality | UNE-EN 14411 | It accomplished all requeriments |
|-------------------------------------------------------------|--------------|----------------------------------|

### PHYSICAL PROPERTIES

|                           |                 |                        |
|---------------------------|-----------------|------------------------|
| Water absorption capacity | EN ISO 10545-03 | >10%                   |
| Flexion resistance        | EN ISO 10545-04 | =>12 N/mm <sup>2</sup> |
| Cracking resistance       | EN ISO 10545-11 | It stands the test     |

### CHEMICAL PROPERTIES

|                                                        |                 |         |
|--------------------------------------------------------|-----------------|---------|
| Resistance to acids                                    | EN ISO 10545-13 | GHB     |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLB     |
| Resistance to cleaning products                        | EN ISO 10545-13 | DCUMPLE |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | CCUMPLE |
| Stains resistance                                      | EN ISO 10545-14 | 3       |

## HURL WHITE RECT 30X90

| REFERENCE      | SIZE (cm) | THICKNESS (mm) | GROUP   |
|----------------|-----------|----------------|---------|
| <b>A039674</b> | 30X90     | 10,40          | REVESTI |



### DIMENSIONS AND SURFACE PROPERTIES

|                                                             |              |                                  |
|-------------------------------------------------------------|--------------|----------------------------------|
| Size, thickness, side straightness, flatness, orthogonality | UNE-EN 14411 | It accomplished all requeriments |
|-------------------------------------------------------------|--------------|----------------------------------|

### PHYSICAL PROPERTIES

|                           |                 |                        |
|---------------------------|-----------------|------------------------|
| Water absorption capacity | EN ISO 10545-03 | >10%                   |
| Flexion resistance        | EN ISO 10545-04 | =>12 N/mm <sup>2</sup> |
| Cracking resistance       | EN ISO 10545-11 | It stands the test     |

### CHEMICAL PROPERTIES

|                                                        |                 |         |
|--------------------------------------------------------|-----------------|---------|
| Resistance to acids                                    | EN ISO 10545-13 | GHB     |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLB     |
| Resistance to cleaning products                        | EN ISO 10545-13 | DCUMPLE |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | CCUMPLE |
| Stains resistance                                      | EN ISO 10545-14 | 3       |

## SCREEN WHITE RECT 30X90

| REFERENCE      | SIZE (cm) | THICKNESS (mm) | GROUP   |
|----------------|-----------|----------------|---------|
| <b>A039563</b> | 30X90     | 10,60          | REVESTI |



### DIMENSIONS AND SURFACE PROPERTIES

|                                                             |              |                                  |
|-------------------------------------------------------------|--------------|----------------------------------|
| Size, thickness, side straightness, flatness, orthogonality | UNE-EN 14411 | It accomplished all requeriments |
|-------------------------------------------------------------|--------------|----------------------------------|

### PHYSICAL PROPERTIES


|                           |                 |                        |
|---------------------------|-----------------|------------------------|
| Water absorption capacity | EN ISO 10545-03 | >10%                   |
| Flexion resistance        | EN ISO 10545-04 | =>12 N/mm <sup>2</sup> |
| Cracking resistance       | EN ISO 10545-11 | It stands the test     |

### CHEMICAL PROPERTIES

|                                                        |                 |         |
|--------------------------------------------------------|-----------------|---------|
| Resistance to acids                                    | EN ISO 10545-13 | GHB     |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLB     |
| Resistance to cleaning products                        | EN ISO 10545-13 | DCUMPLE |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | CCUMPLE |
| Stains resistance                                      | EN ISO 10545-14 | 3       |

## HOSS TAUPE RECT 30X90

| REFERENCE      | SIZE (cm) | THICKNESS (mm) | GROUP   |
|----------------|-----------|----------------|---------|
| <b>A039665</b> | 30X90     | 8,80           | REVESTI |



### DIMENSIONS AND SURFACE PROPERTIES

|                                                             |              |                                  |
|-------------------------------------------------------------|--------------|----------------------------------|
| Size, thickness, side straightness, flatness, orthogonality | UNE-EN 14411 | It accomplished all requeriments |
|-------------------------------------------------------------|--------------|----------------------------------|

### PHYSICAL PROPERTIES

|                           |                 |                        |
|---------------------------|-----------------|------------------------|
| Water absorption capacity | EN ISO 10545-03 | >10%                   |
| Flexion resistance        | EN ISO 10545-04 | =>12 N/mm <sup>2</sup> |
| Cracking resistance       | EN ISO 10545-11 | It stands the test     |

### CHEMICAL PROPERTIES

|                                                        |                 |         |
|--------------------------------------------------------|-----------------|---------|
| Resistance to acids                                    | EN ISO 10545-13 | GHB     |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLB     |
| Resistance to cleaning products                        | EN ISO 10545-13 | DCUMPLE |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | CCUMPLE |
| Stains resistance                                      | EN ISO 10545-14 | 3       |

## HURL TAUPE RECT 30X90

| REFERENCE      | SIZE (cm) | THICKNESS (mm) | GROUP   |
|----------------|-----------|----------------|---------|
| <b>A039676</b> | 30X90     | 10,40          | REVESTI |



### DIMENSIONS AND SURFACE PROPERTIES

|                                                             |              |                                  |
|-------------------------------------------------------------|--------------|----------------------------------|
| Size, thickness, side straightness, flatness, orthogonality | UNE-EN 14411 | It accomplished all requeriments |
|-------------------------------------------------------------|--------------|----------------------------------|

### PHYSICAL PROPERTIES

|                           |                 |                        |
|---------------------------|-----------------|------------------------|
| Water absorption capacity | EN ISO 10545-03 | >10%                   |
| Flexion resistance        | EN ISO 10545-04 | =>12 N/mm <sup>2</sup> |
| Cracking resistance       | EN ISO 10545-11 | It stands the test     |

### CHEMICAL PROPERTIES

|                                                        |                 |         |
|--------------------------------------------------------|-----------------|---------|
| Resistance to acids                                    | EN ISO 10545-13 | GHB     |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLB     |
| Resistance to cleaning products                        | EN ISO 10545-13 | DCUMPLE |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | CCUMPLE |
| Stains resistance                                      | EN ISO 10545-14 | 3       |

## SCREEN TAUPE RECT 30X90

| REFERENCE      | SIZE (cm) | THICKNESS (mm) | GROUP   |
|----------------|-----------|----------------|---------|
| <b>A039666</b> | 30X90     | 10,00          | REVESTI |



### DIMENSIONS AND SURFACE PROPERTIES

|                                                             |              |                                  |
|-------------------------------------------------------------|--------------|----------------------------------|
| Size, thickness, side straightness, flatness, orthogonality | UNE-EN 14411 | It accomplished all requeriments |
|-------------------------------------------------------------|--------------|----------------------------------|

### PHYSICAL PROPERTIES

|                           |                 |                        |
|---------------------------|-----------------|------------------------|
| Water absorption capacity | EN ISO 10545-03 | >10%                   |
| Flexion resistance        | EN ISO 10545-04 | =>12 N/mm <sup>2</sup> |
| Cracking resistance       | EN ISO 10545-11 | It stands the test     |

### CHEMICAL PROPERTIES

|                                                        |                 |         |
|--------------------------------------------------------|-----------------|---------|
| Resistance to acids                                    | EN ISO 10545-13 | GHB     |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLB     |
| Resistance to cleaning products                        | EN ISO 10545-13 | DCUMPLE |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | CCUMPLE |
| Stains resistance                                      | EN ISO 10545-14 | 3       |

## HOSS ASH RECT 30X90

| REFERENCE      | SIZE (cm) | THICKNESS (mm) | GROUP   |
|----------------|-----------|----------------|---------|
| <b>A039555</b> | 30X90     | 8,70           | REVESTI |



### DIMENSIONS AND SURFACE PROPERTIES

|                                                             |              |                                  |
|-------------------------------------------------------------|--------------|----------------------------------|
| Size, thickness, side straightness, flatness, orthogonality | UNE-EN 14411 | It accomplished all requeriments |
|-------------------------------------------------------------|--------------|----------------------------------|

### PHYSICAL PROPERTIES


|                           |                 |                        |
|---------------------------|-----------------|------------------------|
| Water absorption capacity | EN ISO 10545-03 | >10%                   |
| Flexion resistance        | EN ISO 10545-04 | =>12 N/mm <sup>2</sup> |
| Cracking resistance       | EN ISO 10545-11 | It stands the test     |

### CHEMICAL PROPERTIES

|                                                        |                 |         |
|--------------------------------------------------------|-----------------|---------|
| Resistance to acids                                    | EN ISO 10545-13 | GHB     |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLB     |
| Resistance to cleaning products                        | EN ISO 10545-13 | DCUMPLE |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | CCUMPLE |
| Stains resistance                                      | EN ISO 10545-14 | 3       |

## HOSS CINNAMON RECT 30X90

| REFERENCE      | SIZE (cm) | THICKNESS (mm) | GROUP   |
|----------------|-----------|----------------|---------|
| <b>A039556</b> | 30X90     | 8,80           | REVESTI |



### DIMENSIONS AND SURFACE PROPERTIES

|                                                             |              |                                  |
|-------------------------------------------------------------|--------------|----------------------------------|
| Size, thickness, side straightness, flatness, orthogonality | UNE-EN 14411 | It accomplished all requeriments |
|-------------------------------------------------------------|--------------|----------------------------------|

### PHYSICAL PROPERTIES


|                           |                 |                        |
|---------------------------|-----------------|------------------------|
| Water absorption capacity | EN ISO 10545-03 | >10%                   |
| Flexion resistance        | EN ISO 10545-04 | =>12 N/mm <sup>2</sup> |
| Cracking resistance       | EN ISO 10545-11 | It stands the test     |

### CHEMICAL PROPERTIES

|                                                        |                 |         |
|--------------------------------------------------------|-----------------|---------|
| Resistance to acids                                    | EN ISO 10545-13 | GHB     |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLB     |
| Resistance to cleaning products                        | EN ISO 10545-13 | DCUMPLE |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | CCUMPLE |
| Stains resistance                                      | EN ISO 10545-14 | 3       |

## HURL CINNAMON RECT 30X90

| REFERENCE      | SIZE (cm) | THICKNESS (mm) | GROUP   |
|----------------|-----------|----------------|---------|
| <b>A039677</b> | 30X90     | 10,50          | REVESTI |



### DIMENSIONS AND SURFACE PROPERTIES

|                                                             |              |                                  |
|-------------------------------------------------------------|--------------|----------------------------------|
| Size, thickness, side straightness, flatness, orthogonality | UNE-EN 14411 | It accomplished all requeriments |
|-------------------------------------------------------------|--------------|----------------------------------|

### PHYSICAL PROPERTIES

|                           |                 |                        |
|---------------------------|-----------------|------------------------|
| Water absorption capacity | EN ISO 10545-03 | >10%                   |
| Flexion resistance        | EN ISO 10545-04 | =>12 N/mm <sup>2</sup> |
| Cracking resistance       | EN ISO 10545-11 | It stands the test     |

### CHEMICAL PROPERTIES

|                                                        |                 |         |
|--------------------------------------------------------|-----------------|---------|
| Resistance to acids                                    | EN ISO 10545-13 | GHB     |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLB     |
| Resistance to cleaning products                        | EN ISO 10545-13 | DCUMPLE |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | CCUMPLE |
| Stains resistance                                      | EN ISO 10545-14 | 3       |